



Merkmale

Verwendung: Innen
Montageart: WANDMONTAGE, IM GIPSKARTON EINGEBAUT, AUFHÄNGELEUCHTEN, DECKENMONTAGE, SCHIENE
Emission: DIREKTE
Optik: OPAL
Farbe: SCHWARZ
Dimmung: PUSH, DALI
Notfall: NO
L: 1680mm
A: 53mm
H: 69mm
Hergestellt in: ITALY
Garantie: 5 Jahre
Gewicht: 4.2kg

Technische Daten

Eingangsleistung der Leuchte: 40.5W
Lichtstrom der Leuchte: 3220lm
IP: 40
Isolationsklasse: I
Nr. der Treiber pro Produkt: 1
Versorgungsspannung: 220-240V 50/60Hz
SELV: Si

Quelle

Lichtquelle: LED
Leistung der Stromquelle: 36W
Farbtemperatur: 4000K
CRI: >90
Farbtoleranz: 3 Step MacAdam
Lebensdauer LED: 50000h L80 B20

Konformität

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Normen

Photobiologisches Risiko: RISIKOGRUPPE 0Zertifiziertes Gerät in der RISIKO-FREIEN GRUPPE, in Übereinstimmung mit der Bestimmung CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: Gemäß dem CAM EDILIZIA-Bauministerialerlass vom 23. Juni 2022 n.256.

[Weitere Informationen über das Produkt](#)



Merkmale

Verwendung: Innen

Optik: OPAL

L: 1680mm

A: 48mm

H: 6mm

Hergestellt in: ITALY

Garantie: 5 Jahre

Gewicht: 0.4kg

Technische Daten

IP: 40



Technical drawing of the HERO: MOD.CIECO 250 NE profile. It shows a cross-section with dimensions: H 135, L 250, W 90. The profile is a simple extruded shape.	HERO: MOD.CIECO 250 NE	108676.02
Technical drawing of the HERO: MOD.CIECO ANG.DX 150 NE profile. It shows a cross-section with dimensions: H 135, L 150x150, W 90. The profile is an L-shaped extrusion.	HERO: MOD.CIECO ANG.DX 150 NE	108678.02
Technical drawing of the HERO: COPPIA TESTATE NE profile. It shows a cross-section with dimensions: H 135, L 2, W 90. The profile is a thin rectangular extrusion.	HERO: COPPIA TESTATE NE	108684.02
Technical drawing of the HERO: MOD.CIECO ANG.SX 150 NE profile. It shows a cross-section with dimensions: H 135, L 150x150, W 90. The profile is an L-shaped extrusion, similar to the DX version but with different orientation.	HERO: MOD.CIECO ANG.SX 150 NE	108677.02
Technical drawing of the HERO: MOD.CIECO 1680 NE profile. It shows a cross-section with dimensions: H 135, L 1680, W 90. The profile is a long, thin extrusion.	HERO: MOD.CIECO 1680 NE	108681.02
Technical drawing of the HERO: MOD.CIECO 1120 NE profile. It shows a cross-section with dimensions: H 135, L 1120, W 90. The profile is a long, thin extrusion.	HERO: MOD.CIECO 1120 NE	108679.02
Technical drawing of the HERO: MOD.CIECO 1400 NE profile. It shows a cross-section with dimensions: H 135, L 1400, W 90. The profile is a long, thin extrusion.	HERO: MOD.CIECO 1400 NE	108680.02

	HERO: STAFFA PARETE "L" NE	108687.02
	KIT ALIMENTAZIONE L1200 5P BIA	108921.01
	HERO: SOSPL3000 1PZ. TESTA/CODA	108685.99
	KIT ALIMENTAZIONE L3000 5P BIA	108922.01

	KIT ALIMENTAZIONE L3000 5P NE	108922.02
	HERO: SPESS. CARTONG. 10MM 2PZ.	108689.99
	HERO: SOSP.L3000 1PZ. UNIONE	108686.99
	ALL-TRACK: COPPIA ADATT. 3P+DALI NER	106723.02
	HERO: SOSP.L3000 1PZ TESTA W.G.ALTO	1086A1.99
	HERO: KIT INCASSO LED (1X)	108688.99
	KIT ALIMENTAZIONE L1200 5P NE	108921.02
	HERO: SOSP.L3000 1PZ UNIONE W.G.ALTO	1086A2.99