


LUCKY EVO B

1002D8.01 + 1002E6.99

LUCKY EVO B: HF D/I 120W L2811 4KBI DALI + LUCKY EVO B: DIFF.TRAS.+MICROS.PER



novalux
ITALIAN LIGHTING DESIGN SINCE 1948



Features

Use: Indoor
Type of installation: SUSPENDED
Emission: DIRECT/INDIRECT
Optics: MICRO-STRUCTURED
Colour: WHITE
Dimming: DALI
Emergency: NO
L: 2811mm
A: 52mm
H: 91mm
Made in: ITALY
Warranty: 5 years
Weight: 9.4kg

Tech data

Luminaire input power: 132.7W
Luminaire luminous flux: 11560lm
Indirect luminous flux: 6678lm
IP: 40
Insulation class: I
Supply voltage: 220-240V 50/60Hz
UGR: <19
SELV: Si

Source

Light source: LED
Source power: 120W
Source luminous flux: 18440lm
Colour temperature: 4000K
CRI: >80
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

[View more product info](#)



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 8/4/2025, 12:06:56


LUCKY EVO B

1002D8.01 + 1002E6.99

LUCKY EVO B: HF D/I 120W L2811 4KBI DALI + LUCKY EVO B: DIFF.TRAS.+MICROS.PER



novalux
ITALIAN LIGHTING DESIGN SINCE 1948




Features

Use: Indoor
Optics: MICRO-STRUCTURED
Emergency: NO
L: 2811mm
A: 48mm
H: 10mm
Made in: ITALY
Warranty: 5 years
Weight: 0.7kg

Tech data

IP: 40
UGR: <19



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 8/4/2025, 12:06:56



LUCKY EVO B

1002D8.01 + 1002E6.99





LUCKY EVO B: HF D/I 120W L2811 4KBI DALI + LUCKY EVO B: DIFF.TRAS.+MICROS.PER

novalux
ITALIAN LIGHTING DESIGN SINCE 1948

COMPLETION ACCESSORIES

	LUCKY EVO B: MODULO CIECO L=1125 BIANCO	100261.01
	LUCKY EVO B: MODULO CIECO L=1406 BIANCO	100262.01
	LUCKY EVO B: MODULO CIECO L=1687 BIANCO	100263.01
	LUCKY EVO B: MODULO CIECO ANG. L=592 BI	100264.01
	LUCKY EVO B: COPPIA TESTATE CHIUSURA BIA	100247.01
	LUCKY EVO B: KIT GIUNZIONE MODULI	100248.01

MOUNTING ACCESSORIES

	KIT ALIMENTAZIONE L1200 3P BIA	108919.01
	KIT ALIMENTAZIONE L3000 3P BIA	108920.01
	KIT ALIMENTAZIONE L1200 5P BIA	108921.01
	KIT ALIMENTAZIONE L3000 5P BIA	108922.01
	LUCKY EVO B: KIT COPPIA CAVI SOSP. 5 M	1002B5.99



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 8/4/2025, 12:06:56