




LUCKY EVO B

1002K1.02

novalux
ITALIAN LIGHTING DESIGN SINCE 1948



Features

Use: Indoor
Type of installation: SUSPENDED
Emission: INDIRECT
Optics: OPAL
Colour: BLACK
Dimming: DALI
Emergency: NO
L: 1125mm
A: 52mm
H: 91mm
Made in: ITALY
Warranty: 5 years
Weight: 4.217kg

Tech data

Luminaire input power: 20W
Indirect luminous flux: 2226lm
IP: 40
Insulation class: I
Supply voltage: 220-240V 50/60Hz
SELV: Si

Source

Light source: LED
Source power: 18W
Source luminous flux: 2935lm
Colour temperature: 4000K
CRI: >80
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

[View more product info](#)




Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 8/4/2025, 11:43:02


LUCKY EVO B

1002K1.02


COMPLETION ACCESSORIES



LUCKY EVO B: DIFF. CIECO PER L1125 NERO 100257.02



LUCKY EVO B: COPPIA TESTATE CHIUSURA NER 100247.02



LUCKY EVO B: KIT GIUNZIONE MODULI 100248.01

MOUNTING ACCESSORIES



LUCKY EVO B: KIT COPPIA CAVI SOSP. 5 M 1002B5.99



KIT ALIMENTAZIONE L1200 3P NE 108919.02



KIT ALIMENTAZIONE L3000 3P NE 108920.02



KIT ALIMENTAZIONE L1200 5P NE 108921.02



KIT ALIMENTAZIONE L3000 5P NE 108922.02

