


STRIP LED

1009B9.99

novalux
ITALIAN LIGHTING DESIGN SINCE 1948



Features

Use: Indoor, Outdoor
Dimming: WITH ACCESSORY
Emergency: WITH ACCESSORY
L: 10000mm
A: 10mm
Warranty: 5 years
Weight: 1kg

Tech data

Luminous flux in emergency: L min = 90 L max = 410 - 1h: 17% / 3h: 7%
IP: 67
Insulation class: III
Supply voltage: 48 Vdc
SELV: Si

Source

Light source: LED
Source power: 6W/m
Source luminous flux: 710lm
Colour temperature: 4000K
CRI: >90
LED lifespan: 30000h L70 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

[STRIP LED: View more product info](#)



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 29/5/2026, 16:23:41

STRIP LED

1009B9.99

novalux

ITALIAN LIGHTING DESIGN SINCE 1948

COMPLETION ACCESSORIES



STRIP LED 48VDC IP67: KIT TESTATE+CAVO

1009C7.99



STRIP LED 230VAC: SIGILLANTE

100966.99



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 29/5/2026, 16:23:41