



Features

Use: Indoor
Type of installation: TRACK
Emission: ADJUSTABLE
Optics: SPOT
Beam: 25°
Colour: WHITE
Dimming: WITH ACCESSORY
Emergency: NO
H: 70mm
ø: 42mm
Made in: ITALY
Warranty: 5 years

Tech data

Luminaire input power: 5.3W
Luminaire luminous flux: 535lm
IP: 20
Insulation class: III
Supply voltage: 24 Vdc
SELV: Si

Source

Light source: LED
Source power: 5.3W
Source luminous flux: 670lm
Colour temperature: 4000K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L90 B10

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: CAM edilizia - Conforme al Decreto Ministeriale 23 giugno 2022 n.256 e 24 novembre 2025 n.256.

[L-16 SYSTEM: View more product info](#)

[B-16 SYSTEM: View more product info](#)

