



Features

Use: Indoor
 Type of installation: TRACK
 Emission: ADJUSTABLE
 Optics: SPOT
 Beam: 34°
 Colour: BLACK
 Dimming: DALI
 Emergency: NO
 L: 255mm
 A: Ø55mm
 H: 60mm
 Made in: ITALY
 Warranty: 5 years
 Weight: 0.55kg

Tech data

Luminaire input power: 15W
 Luminaire luminous flux: 1115lm
 IP: 20
 Insulation class: II
 No. of driver per product: 1
 Supply voltage: 220-240V 50/60Hz
 SELV: Si

Source

Light source: LED
 Source power: 12W
 Source luminous flux: 1375lm
 Colour temperature: 3000K
 CRI: >90
 Colour tolerance: 2 Step MacAdam
 LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)



COMPLETION ACCESSORIES



GALA: HONEYCOMB D.50

1018A4.02

