

Features

Use: Indoor
Type of installation: RECESSED INTO PLASTERBOARD
Emission: DIRECT
Optics: SPOT
Beam: 55°
Colour: WHITE
Dimming: WITH ACCESSORY
Emergency: WITH ACCESSORY
H: 90mm
ø: 95mm
Warranty: 5 years
Weight: 0.44kg

Tech data

Luminaire luminous flux: 745lm
Luminous flux in emergency: 1h: 44% / 3h: 18
IP: 54
Insulation class: III
Supply voltage: DC 500 mA
SELV: Sì

Source

Light source: LED
Source power: 10W
Source luminous flux: 945lm
Colour temperature: 3000K
CRI: >90
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[WELL/MINI WELL: View more product info](#)

ELECTRICAL ACCESSORIES


	ALIM. LED 14W 500MA/2-27V	101331.99
---	---------------------------	-----------


	ALIM. LED MAX 18W 500MA	101325.99
---	-------------------------	-----------

DIMMABLE ACCESSORIES

	ALIM. LED 26W 500MA/9-52V DALI/PUSH	101334.99
---	-------------------------------------	-----------

EMERGENCY ACCESSORIES

	KIT EMERGENZA 1H 10V-54V	18004.99
---	--------------------------	----------

	KIT EMERGENZA 3H 10V-54V	18005.99
--	--------------------------	----------