

Features

Use: Indoor
Type of installation: SUSPENDED, CEILING MOUNTED
Emission: DIRECT
Optics: OPAL
Colour: BLACK
Dimming: ON/OFF
Emergency: NO
L: 2400mm
A: 38mm
H: 65mm
Made in: ITALY
Warranty: 5 years
Weight: 4.1kg

Tech data

Luminaire input power: 39.1W
Luminaire luminous flux: 3343lm
IP: 40
Insulation class: I
Supply voltage: 220-240V 50/60Hz
SELV: Sì

Source

Light source: LED
Source power: 35W
Source luminous flux: 5802lm
Colour temperature: 3000K
CRI: >80
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[LUCKY MINI: View more product info](#)

LUCKY MINI

103502.02

novalux
ITALIAN LIGHTING DESIGN SINCE 1948

SCREENS



LUCKY MINI: DIFF. OPALE L=6500


103507.99



LUCKY MINI: DIFF. OPALE PER L2400

103506.99

COMPLETION ACCESSORIES



KIT GIUNZIONE MODULI P-30/LUCKY MINI

103317.99



LUCKY MINI: COPPIA TESTATE NE

103509.02

MOUNTING ACCESSORIES



KIT ALIMENTAZIONE L3000 3P NE

108920.02



ALL-TRACK: COPPIA ADATT. 3P NER

106722.02



LUCKY MINI: CAVO DI SOSPENSIONE L=3000

103513.99



KIT ALIMENTAZIONE L1200 3P NE

108919.02



KIT ALIMENTAZIONE L1200 5P NE

108921.02



Novalux S.r.l. via Marzabotto, 2 40050 Fano di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 6/8/2025, 12:56:59