

Features

Use: Indoor
Type of installation: SUSPENDED, CEILING MOUNTED
Emission: DIRECT
Optics: OPAL
Colour: CAPPUCCINO
Dimming: ON/OFF
Emergency: Autonomy 1h/Recharge time 12h
L: 1600mm
A: 38mm
H: 65mm
Made in: ITALY
Warranty: 5 years except battery
Weight: 2.86kg

Tech data

Luminaire input power: 27.3W
Luminaire luminous flux: 2229lm
Luminous flux in emergency: 16%
IP: 40
Insulation class: I
Supply voltage: 220-240V 50/60Hz
SELV: Si

Source

Light source: LED
Source power: 23W
Source luminous flux: 3868lm
Colour temperature: 3000K
CRI: >80
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-22:2023

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[LUCKY MINI: View more product info](#)

LUCKY MINI

103520.21

novalux
ITALIAN LIGHTING DESIGN SINCE 1948

SCREENS



LUCKY MINI: DIFF. OPALE PER L1600

103505.99



LUCKY MINI: DIFF. OPALE L=6500


103507.99

COMPLETION ACCESSORIES



LUCKY MINI: COPPIA TESTATE CAPPUCCINO

103509.21



KIT GIUNZIONE MODULI P-30/LUCKY MINI

103317.99

MOUNTING ACCESSORIES



KIT ALIMENTAZIONE L1200 3P CAP

108919.21



KIT ALIMENTAZIONE L3000 3P CAP

108920.21



LUCKY MINI: CAVO DI SOSPENSIONE L=3000

103513.99



Novalux S.r.l. via Marzabotto, 2 40050 Fano di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 6/8/2025, 12:57:09