


Features

Use: Indoor
Type of installation: SUSPENDED, CEILING MOUNTED
Emission: DIRECT
Optics: OPAL
Colour: WHITE
Dimming: ON/OFF
Emergency: Autonomy 1h/Recharge time 12h
L: 2400mm
A: 38mm
H: 65mm
Made in: ITALY
Warranty: 5 years except battery
Weight: 4.1kg

Tech data

Luminaire input power: 39.1W
Luminaire luminous flux: 3438lm
Luminous flux in emergency: 11%
IP: 40
Insulation class: I
Supply voltage: 220-240V 50/60Hz
SELV: Si

Source

Light source: LED
Source power: 35W
Source luminous flux: 5967lm
Colour temperature: 4000K
CRI: >80
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-22:2023

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

[View more product info](#)

LUCKY MINI

103523.01

novalux
ITALIAN LIGHTING DESIGN SINCE 1948

SCREENS



LUCKY MINI: DIFF. OPALE PER L2400


103506.99



LUCKY MINI: DIFF. OPALE L=6500


103507.99

COMPLETION ACCESSORIES



LUCKY MINI: COPPIA TESTATE BIA


103509.01



KIT GIUNZIONE MODULI P-30/LUCKY MINI


103317.99

MOUNTING ACCESSORIES




LUCKY MINI: CAVO DI SOSPENSIONE L=3000

103513.99




KIT ALIMENTAZIONE L1200 3P BIA

108919.01



KIT ALIMENTAZIONE L3000 3P BIA

108920.01



KIT ALIMENTAZIONE L1200 5P BIA

108921.01



Novalux S.r.l. via Marzabotto, 2 40050 Fano di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 8/4/2025, 11:47:43