

Features

Use: Indoor
Type of installation: SUSPENDED, CEILING MOUNTED
Emission: DIRECT
Optics: OPAL
Colour: CAPPUCCINO
Dimming: ON/OFF
Emergency: Autonomy 1h/Recharge time 12h
L: 2400mm
A: 38mm
H: 65mm
Made in: ITALY
Warranty: 5 years except battery
Weight: 4.1kg

Tech data

Luminaire input power: 39.1W
Luminaire luminous flux: 3438lm
Luminous flux in emergency: 11%
IP: 40
Insulation class: I
Supply voltage: 220-240V 50/60Hz
SELV: Si

Source

Light source: LED
Source power: 35W
Source luminous flux: 5967lm
Colour temperature: 4000K
CRI: >80
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-22:2023

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[LUCKY MINI: View more product info](#)

SCREENS



LUCKY MINI: DIFF. OPALE PER L2400

103506.99



LUCKY MINI: DIFF. OPALE L=6500


103507.99

COMPLETION ACCESSORIES



LUCKY MINI: COPPIA TESTATE CAPPUCCINO

103509.21



KIT GIUNZIONE MODULI P-30/LUCKY MINI

103317.99

MOUNTING ACCESSORIES



KIT ALIMENTAZIONE L1200 3P CAP

108919.21



KIT ALIMENTAZIONE L3000 3P CAP

108920.21



LUCKY MINI: CAVO DI SOSPENSIONE L=3000

103513.99