

Features

Use: Indoor
Type of installation: SUSPENDED, CEILING MOUNTED
Emission: DIRECT
Optics: OPAL
Colour: CAFFE
Dimming: ON/OFF
Emergency: NO
L: 800mm
A: 38mm
H: 65mm
Made in: ITALY
Warranty: 5 years
Weight: 1.5kg

Tech data

Luminaire input power: 14.6W
Luminaire luminous flux: 1114lm
IP: 40
Insulation class: I
Supply voltage: 220-240V 50/60Hz
SELV: Sì

Source

Light source: LED
Source power: 12W
Source luminous flux: 1934lm
Colour temperature: 3000K
CRI: >80
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[LUCKY MINI: View more product info](#)

SCREENS



LUCKY MINI: DIFF. OPALE PER L800

103510.99



LUCKY MINI: DIFF. OPALE L=6500


103507.99

COMPLETION ACCESSORIES



LUCKY MINI: COPPIA TESTATE CAFFEA

103509.20



KIT GIUNZIONE MODULI P-30/LUCKY MINI


103317.99

MOUNTING ACCESSORIES




KIT ALIMENTAZIONE L1200 3P CAF

108919.20



KIT ALIMENTAZIONE L3000 3P CAF

108920.20



LUCKY MINI: CAVO DI SOSPENSIONE L=3000

103513.99