

Features

Use: Indoor
Type of installation: RECESSED INTO PLASTERBOARD
Emission: DIRECT
Optics: SPOT
Beam: 55°
Colour: WHITE
Dimming: WITH ACCESSORY
Emergency: WITH ACCESSORY
H: 121mm
ø: 80mm
Warranty: 5 years
Weight: 0.45kg

Tech data

Luminaire luminous flux: 1648lm
Luminous flux in emergency: 1h: 23% / 3h: 9
IP: 20
Insulation class: III
Supply voltage: DC 500 mA
SELV: Sì

Source

Light source: LED
Source power: 18W
Colour temperature: 4000K
CRI: >90
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[KONE: View more product info](#)

ELECTRICAL ACCESSORIES



ALIM. LED MAX 18W 500MA

101325.99

DIMMABLE ACCESSORIES



ALIM. LED 26W 500MA/9-52V DALI/PUSH


101334.99

EMERGENCY ACCESSORIES



KIT EMERGENZA 1H 10V-54V

18004.99



KIT EMERGENZA 3H 10V-54V

18005.99