




Features

Use: Indoor
Type of installation: RECESSED INTO BRICKWORK, RECESSED INTO PLASTERBOARD
Emission: DIRECT
Optics: SPOT
Beam: 36°
Colour: WHITE
Dimming: WITH ACCESSORY
Emergency: WITH ACCESSORY
L: 90mm
A: 90mm
H: 77mm
Warranty: 5 years
Weight: 0.385kg

Tech data

Luminaire luminous flux: 832lm
Luminous flux in emergency: 67%
IP: 54
Insulation class: III
Supply voltage: DC 500 mA
SELV: No

Source

Light source: LED
Source power: 10W
Source luminous flux: 1010lm
Colour temperature: 4000K
CRI: >90
LED lifespan: 30000h L70 B20

Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-2


Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[PIX: View more product info](#)

MOUNTING ACCESSORIES



PIX: CASSAFORMA PER PIX QUADRATO

103705.99

ELECTRICAL ACCESSORIES



ALIM. LED 15W/500MA

101307.99

DIMMABLE ACCESSORIES



ALIM. MAX.20W/500MA DALI/PUSH/0-10V/1-10

101904.99