



Features

Use: Indoor
Type of installation: RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED
Emission: DIRECT
Optics: LENS UGR<19
Colour: WHITE
Dimming: ON/OFF
Emergency: WITH ACCESSORY
L: 595mm
A: 595mm
H: 14 (30 con alim.)mm
Warranty: 5 years
Weight: 3.4kg

Tech data

Luminaire input power: 34W
Luminaire luminous flux: 4000lm
Luminous flux in emergency: 1h: 13% / 3h: 5%
IP: 40
Insulation class: II
No. of driver per product: 1
Supply voltage: 900 mA ALIMENT.INCLUSO
UGR: <19
SELV: Si

Source

Light source: LED
Source power: 30W
Source luminous flux: 4895lm
Colour temperature: 4000K
CRI: >90
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.
Conto Termico (Thermal account): Compliant with Ministerial Decree for economic development for thermal account and Ministerial Decree for Energy management (GSE) of 16 February 2016. Compliant with Safety Criteria, Electromagnetic Compatibility and Photometric Data certified by accredited laboratory.

Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2012).

[View more product info](#)



MOUNTING ACCESSORIES

	<p>BOX PER INST. PLAFONE THE PANEL 600X600</p>	<p>102086.01</p>
	<p>SCHOOL: KIT MOLLE PER INCASSO</p>	<p>104107.99</p>
	<p>THE PANEL 2: KIT INST.INC.RAS.CART.600</p>	<p>102028.99</p>
	<p>SCHOOL: KIT ANTICADUTA L=3000</p>	<p>104119.99</p>
	<p>KIT ALIMENTAZIONE L1200 3P BIA</p>	<p>108919.01</p>
	<p>SCHOOL: KIT SOSPENSIONE H1200</p>	<p>104110.99</p>
	<p>SCHOOL: KIT INST.PLAFONE 600X600</p>	<p>104108.01</p>

EMERGENCY ACCESSORIES

	<p>THE PANEL 2: EMER.INC.3H 10/54VDC</p>	<p>1020A5.99</p>
	<p>THE PANEL 2: EMER.INC.1H 10/54VDC</p>	<p>1020A4.99</p>