

Features

Use: Indoor
Type of installation: RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED
Emission: DIRECT
Optics: LENS UGR<19
Colour: WHITE
Dimming: ON/OFF
Emergency: WITH ACCESSORY
L: 1125mm
A: 295mm
H: 14 (30 con alim.)mm
Warranty: 5 years
Weight: 4.0kg

Tech data

Luminaire input power: 56W
Luminaire luminous flux: 6832lm
Luminous flux in emergency: 1h: 8% / 3h: 3%
IP: 40
Insulation class: II
No. of driver per product: 1
Supply voltage: 1500 mA ALIMENT.INCLUSO
UGR: <19
SELV: Si

Source

Light source: LED
Source power: 50W
Source luminous flux: 8359lm
Colour temperature: 4000K
CRI: >90
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.
Conto Termico (Thermal account): Compliant with Ministerial Decree for economic development for thermal account and Ministerial Decree for Energy management (GSE) of 16 February 2016. Compliant with Safety Criteria, Electromagnetic Compatibility and Photometric Data certified by accredited laboratory.




Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2012).



[View more product info](#)



MOUNTING ACCESSORIES

	SCHOOL: KIT MOLLE PER INCASSO	104107.99
	SCHOOL: KIT ANTICADUTA L=3000	104119.99
	KIT ALIMENTAZIONE L1200 3P BIA	108919.01
	BOX PER INST. PLAFONE THE PANEL 1200X300	102087.01
	SCHOOL: KIT INST.PLAFONE 1200X300	104109.01
	THE PANEL 2: KIT INST.INC.RAS.CART.1200	102029.99
	SCHOOL: KIT SOSPENSIONE H1200	104110.99

EMERGENCY ACCESSORIES

	THE PANEL 2: EMER.INC.3H 10/54VDC	1020A5.99
	THE PANEL 2: EMER.INC.1H 10/54VDC	1020A4.99