

## Features

Use: Indoor  
 Type of installation: RECESSED INTO PLASTERBOARD, SUSPENDED  
 Emission: DIRECT  
 Optics: LENS UGR<19  
 Colour: WHITE  
 Dimming: PUSH, DALI  
 Emergency: WITH ACCESSORY  
 L: 595mm  
 A: 595mm  
 H: 14 (30 con driver)mm  
 Warranty: 5 years  
 Weight: 3.4kg

## Tech data

Luminaire input power: 34W  
 Luminaire luminous flux: 4000lm  
 Luminous flux in emergency: 1h: 13% / 3h: 5%  
 IP: 40  
 Insulation class: II  
 Supply voltage: 900MA ALIMENT.INCLUSO  
 UGR: <19  
 SELV: No

## Source

Light source: LED  
 Source power: 30W  
 Source luminous flux: 4895lm  
 Colour temperature: 4000K  
 CRI: >90  
 LED lifespan: 50000h L80 B20

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012





## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.  
 CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.



## Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2012).

**MOUNTING ACCESSORIES**

|   |  |                  |
|---|--|------------------|
|  | KIT ALIMENTAZIONE L1200 5P BIA         | <b>108921.01</b> |
|   | THE PANEL 2: KIT INST.INC.RAS.CART.600 | <b>102028.99</b> |
|   | SCHOOL: KIT ANTICADUTA L=3000          | <b>104119.99</b> |
|   | SCHOOL: KIT SOSPENSIONE H1200          | <b>104110.99</b> |

**EMERGENCY ACCESSORIES**

|  |                                   |                  |
|--|-----------------------------------|------------------|
|  | THE PANEL 2: EMER.INC.3H 10/54VDC | <b>1020A5.99</b> |
|  | THE PANEL 2: EMER.INC.1H 10/54VDC | <b>1020A4.99</b> |