

Features

Use: Indoor
 Type of installation: RECESSED INTO PLASTERBOARD, SUSPENDED
 Emission: DIRECT
 Optics: LENS UGR<19
 Colour: WHITE
 Dimming: PUSH, DALI
 Emergency: WITH ACCESSORY
 L: 595mm
 A: 595mm
 H: 14 (30 con driver)mm
 Warranty: 5 years
 Weight: 3.4kg

Tech data

Luminaire input power: 34W
 Luminaire luminous flux: 4000lm
 Luminous flux in emergency: 1h: 13% / 3h: 5
 IP: 40
 Insulation class: II
 Supply voltage: 900mA driver incluso
 UGR: <19
 SELV: Sì

Source

Light source: LED
 Source power: 30W
 Source luminous flux: 4895lm
 Colour temperature: 4000K
 CRI: >90
 LED lifespan: 50000h L80 B20

Compliance


CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
 CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2012).

MOUNTING ACCESSORIES


SCHOOL: KIT INST.PLAFONE 600X600

104108.01


SCHOOL: KIT MOLLE PER INCASSO

104107.99

SCHOOL: KIT SOSPENSIONE H1200

104110.99


KIT ALIMENTAZIONE L1200 5P BIA

108921.01


THE PANEL 2: KIT INST.INC.RAS.CART.600

102028.99

SCHOOL: KIT ANTICADUTA L=3000

104119.99
EMERGENCY ACCESSORIES


THE PANEL 2: EMER.INC.1H 10/54VDC

1020A4.99

THE PANEL 2: EMER.INC.3H 10/54VDC

1020A5.99