

## Features

Use: Indoor  
Type of installation: RECESSED INTO PLASTERBOARD  
Emission: DIRECT  
Optics: SPOT  
Beam: 68°  
Colour: WHITE  
Dimming: WITH ACCESSORY  
Emergency: WITH ACCESSORY  
A: Ø225mm  
H: 71mm  
D: 200mm  
Warranty: 5 years  
Weight: 0.95kg

## Tech data

Luminaire input power: 28W  
Luminaire luminous flux: 2750lm  
Luminous flux in emergency: 25%  
IP: 40  
Insulation class: II  
Supply voltage: 220-240V 50/60Hz  
UGR: <19  
SELV: Si

## Source

Light source: LED  
Source power: 25W  
Source luminous flux: 3159lm  
Colour temperature: 3000K  
CRI: >80  
LED lifespan: 30000h L70 B20

## Compliance


CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-2

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

[View more product info](#)


## COMPLETION ACCESSORIES



SLIM: ADATT.PER FORO 240MM / 250MM

**11814.01**


## DIMMABLE ACCESSORIES



ALIM. LED DALI/PUSH 24.5W/550MA 20-45V


**101324.99**

## EMERGENCY ACCESSORIES



KIT EMERGENZA 1H 9V-58V

**18002.99**



KIT EMERGENZA 3H 9V-58V

**18003.99**