



## Features

Use: Indoor  
Type of installation: WALL, CEILING MOUNTED  
Emission: DIRECT  
Optics: OPAL  
Colour: WHITE  
Dimming: ON/OFF  
Emergency: Autonomy 1h/Recharge time 12h  
L: Ø400mm  
H: 58mm  
Warranty: 5 years  
Weight: 2.4kg

## Tech data

Luminaire input power: 40W  
Luminaire luminous flux: 4209lm  
Luminous flux in emergency: 8%  
IP: 44  
Insulation class: II  
No. of driver per product: 1  
Supply voltage: 220-240V 50/60Hz

## Source

Light source: LED  
Source power: 36W  
Source luminous flux: 5050lm  
Colour temperature: 4000K  
CRI: >90  
LED lifespan: 50000h L70 B30

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-22:2023

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.  
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[LUNA: View more product info](#)