



Features

Use: Indoor
Type of installation: WALL, SUSPENDED, CEILING MOUNTED
Emission: DIRECT
Optics: OPAL
Colour: WHITE
Dimming: PUSH, DALI
Emergency: NO
L: 400mm
A: 400mm
H: 81mm
Made in: ITALY
Warranty: 5 years
Weight: 3.8kg

Tech data

Luminaire input power: 35.2W
Luminaire luminous flux: 3443lm
IP: 40
Insulation class: I
Supply voltage: 220-240V 50/60Hz
SELV: Si

Source

Light source: LED
Source power: 31W
Source luminous flux: 5062lm
Colour temperature: 4000K
CRI: >80
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

[ROTO: View more product info](#)

MOUNTING ACCESSORIES

	ROTO: D=400 KIT 3 SOSP. L3000	104413.99
	ROTO: ALIMENTAZIONE L1200 5P. BIA.	104424.01
	ROTO: ALIMENTAZIONE L3000 5P. BIA.	104426.01