



Features

Use: Indoor
Type of installation: SUSPENDED
Emission: DIRECT/INDIRECT
Optics: OPAL
Colour: WHITE
Dimming: ON/OFF
Emergency: NO
L: 800mm
A: 800mm
H: 81mm
Made in: ITALY
Warranty: 5 years
Weight: 12kg

Tech data

Luminaire input power: 116.4W
Luminaire luminous flux: 11158lm
Direct luminous flux: 7770lm
Indirect luminous flux: 3388lm
IP: 40
Insulation class: I
Supply voltage: 220-240V 50/60Hz
SELV: No

Source

Light source: LED
Source power: 105W
Source luminous flux: 16353lm
Colour temperature: 3000K
CRI: >80
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

[ROTO: View more product info](#)

MOUNTING ACCESSORIES

	ROTO: ALIMENTAZIONE L1200 3P. BIA	104423.01
	ROTO: ALIMENTAZIONE L1200 5P. BIA.	104424.01
	ROTO: ALIMENTAZIONE L3000 3P. BIA.	104425.01
	ROTO: ALIMENTAZIONE L3000 5P. BIA.	104426.01
	ROTO: D=800 KIT 4 SOSP. L3000	104428.99