



Features

Use: Indoor
Type of installation: SUSPENDED
Emission: DIRECT/INDIRECT
Optics: OPAL
Colour: WHITE
Dimming: PUSH, DALI
Emergency: NO
L: 1200mm
A: 1200mm
H: 90mm
Made in: ITALY
Warranty: 5 years
Weight: 28kg

Tech data

Luminaire input power: 213.4W
Luminaire luminous flux: 23422lm
Direct luminous flux: 16388lm
Indirect luminous flux: 7034lm
IP: 40
Insulation class: I
Supply voltage: 220-240V 50/60Hz
SELV: No

Source

Light source: LED
Source power: 192W
Source luminous flux: 32106lm
Colour temperature: 4000K
CRI: >80
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

[View more product info](#)

MOUNTING ACCESSORIES



ROTO: ALIMENTAZIONE L1200 5P. BIA.

104424.01



ROTO: ALIMENTAZIONE L3000 5P. BIA.

104426.01



ROTO: D=1200 KIT 4 SOSP. L3000

104429.99