



Features

Use: Indoor
Type of installation: RECESSED INTO PLASTERBOARD
Emission: DIRECT
Optics: OPAL
Dimming: PUSH, DALI
Emergency: NO
L: 800mm
A: 800mm
H: 90mm
D: 825mm
Made in: ITALY
Warranty: 5 years
Weight: 12.6kg

Tech data

Luminaire input power: 69.7W
Luminaire luminous flux: 7770lm
IP: 20
Insulation class: I
Supply voltage: 220-240V 50/60Hz
SELV: Si

Source

Light source: LED
Source power: 63W
Source luminous flux: 10474lm
Colour temperature: 3000K
CRI: >80
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[ROTO: View more product info](#)

MOUNTING ACCESSORIES

	ROTO: ALIMENTAZIONE L1200 5P. BIA.	104424.01
	ROTO: ALIMENTAZIONE L3000 5P. BIA.	104426.01
	ROTO: D=800 KIT 4 SOSP. L3000	104428.99