



Features

Use: Indoor
Type of installation: RECESSED INTO PLASTERBOARD
Emission: DIRECT
Optics: OPAL
Dimming: ON/OFF
Emergency: NO
L: 1200mm
A: 1200mm
H: 90mm
D: 1225mm
Made in: ITALY
Warranty: 5 years
Weight: 18.4kg

Tech data

Luminaire input power: 119.4W
Luminaire luminous flux: 16388lm
IP: 20
Insulation class: I
Supply voltage: 220-240V 50/60Hz
SELV: Si

Source

Light source: LED
Source power: 108W
Source luminous flux: 19998lm
Colour temperature: 4000K
CRI: >80
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[ROTO: View more product info](#)

MOUNTING ACCESSORIES

	ROTO: ALIMENTAZIONE L1200 3P. BIA	104423.01
	ROTO: ALIMENTAZIONE L3000 3P. BIA.	104425.01
	ROTO: D=1200 KIT 4 SOSP. L3000	104429.99