

Features

Use: Indoor
Type of installation: RECESSED INTO PLASTERBOARD
Emission: DIRECT
Optics: OPAL
Colour: WHITE
Dimming: PUSH, DALI
Emergency: WITH ACCESSORY
L: 595mm
A: 595mm
H: 12mm
Warranty: 5 years
Weight: 0.855kg

Tech data

Luminaire input power: 38W
Luminaire luminous flux: 4334lm
Luminous flux in emergency: 1h: 12% / 3h: 5
IP: 40
Insulation class: II
No. of driver per product: 1
Supply voltage: 950 mA ALIMENT.INCLUSO
SELV: Si

Source

Light source: LED
Source power: 35W
Source luminous flux: 4904lm
Colour temperature: 3000K
CRI: >80
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards


Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[FRAME PANEL: View more product info](#)



FRAME PANEL

104711.01

MOUNTING ACCESSORIES

	THE PANEL 2: KIT INST.INC.RAS.CART.600	102028.99
--	--	-----------

EMERGENCY ACCESSORIES

	THE PANEL 2: EMER.INC.1H 10/54VDC	1020A4.99
	THE PANEL 2: EMER.INC.3H 10/54VDC	1020A5.99