



Features

Use: Indoor
Type of installation: WALL, SUSPENDED, CEILING MOUNTED
Emission: INTERNAL
Optics: OPAL
Colour: WHITE
Dimming: WITH ACCESSORY
Emergency: NO
L: Ø962mm
A: 40mm
H: 45mm
Made in: ITALY
Warranty: 5 years
Weight: 6.2kg

Tech data

Luminaire input power: 66.1W
Luminaire luminous flux: 3005lm
IP: 40
Insulation class: III
Supply voltage: MAX 1.8A
IK: 3
SELV: Si

Source

Light source: LED
Source power: 62W
Source luminous flux: 8456lm
Colour temperature: 2700K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[HALOS: View more product info](#)

COMPLETION ACCESSORIES



ARK/HALOS: KIT GIUNZIONE PROFILI BIA

109809.01

MOUNTING ACCESSORIES



CAVO ALIMENTAZIONE L=3000 2X1 BIANCO

109001.01



CAVO ALIMENTAZIONE L=3000 3X1.5 TRASP

109001.00



HALOS: ROSONE DOPPIA ALIM. REMOTA BIA

105158.01



HALOS: KIT 4 CAVI SOSPENSIONE L.3000

105159.99



HALOS: ROSONE ALIM. REMOTA BIA

105157.01



CAVO ALIMENTAZIONE L=3000 2X1 NERO

109001.02

ELECTRICAL ACCESSORIES



HALOS: ROSONE-N DOPPIA ALIM ON/OFF BIA

105155.01



HALOS: ROSONE-N ALIM. ON/OFF BIA

105151.01



HALOS: ROSONE ALIM. ON/OFF BIANCO

105149.01



HALOS: ROSONE DOPPIA ALIM. ON/OFF BIA 105153.01



HALOS: ALIMENTATORE ON/OFF 105147.99

DIMMABLE ACCESSORIES



HALOS: ROSONE-N ALIM. DALI/PUSH BIA 105152.01



HALOS: ROSONE ALIM. DALI/PUSH BIANCO 105150.01



HALOS: ALIMENTATORE DALI/PUSH 105148.99



HALOS: ROSONE-N DOPPIA ALIM D/PUSH BIA 105156.01



HALOS: ROSONE DOPPIA ALIM. DA/PUSH BIA 105154.01