




# P-30 PCB

105830.02

**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948



## Features

Use: Indoor  
Type of installation: WALL  
Emission: DIRECT, INDIRECT  
Optics: OPAL  
Colour: BLACK  
Dimming: ON/OFF  
Emergency: NO  
L: 1600mm  
A: 31mm  
H: 31mm  
Made in: ITALY  
Warranty: 5 years  
Weight: 1.62kg

## Tech data

Luminaire input power: 19.9W  
Luminaire luminous flux: 1575lm  
IP: 40  
Insulation class: I  
No. of driver per product: 1  
Supply voltage: 220-240V 50/60Hz  
SELV: Si

## Source

Light source: LED  
Source power: 16W  
Source luminous flux: 2968lm  
Colour temperature: 3000K  
CRI: >90  
Colour tolerance: 3 Step MacAdam  
LED lifespan: 50000h L90 B10

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.  
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[P-30 PCB: View more product info](#)



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: [info@novalux.it](mailto:info@novalux.it) · VAT number 00536541204 · [novalux.com](http://novalux.com)  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.  
Last update: 6/8/2025, 12:54:36



# P-30 PCB

105830.02

## SCREENS

|                                                                                  |                            |           |
|----------------------------------------------------------------------------------|----------------------------|-----------|
|  | P-30: DIFF. OPALEPER L1600 | 103313.99 |
|  | P-30: DIFF. OPALE L=6500   | 103315.99 |

## COMPLETION ACCESSORIES

|                                                                                    |                                         |           |
|------------------------------------------------------------------------------------|-----------------------------------------|-----------|
|   | P-30: ANGOLO L PLAFONE-SOSP-PARETE NERO | 103327.02 |
|   | P-30: COVER ANGOLO L NERO               | 103329.02 |
|  | P-30: TESTATE PLAF/SOSP/PAR/SPOT NERO   | 103361.02 |
|  | P-30: SNODO 3P PER PCB/STRIP NERO       | 105853.02 |
|  | P-30: SNODO NO CAVI NERO                | 105854.02 |