

# P-30 PCB

105897.20

**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948



## Features

Use: Indoor  
Type of installation: WALL  
Emission: DIRECT, INDIRECT  
Optics: OPAL  
Colour: CAFFE  
Dimming: ON/OFF  
Emergency: NO  
L: 800mm  
A: 31mm  
H: 31mm  
Made in: ITALY  
Warranty: 5 years

## Tech data

Luminaire input power: 11.1W  
Luminaire luminous flux: 740lm  
IP: 40  
Insulation class: I  
No. of driver per product: 1  
Supply voltage: 220-240V 50/60Hz  
SELV: Si

## Source

Light source: LED  
Source power: 8W  
Source luminous flux: 1394lm  
Colour temperature: 2700K  
CRI: >90  
Colour tolerance: 3 Step MacAdam  
LED lifespan: 50000h L80 B20

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.  
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[P-30 PCB: View more product info](#)



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: [info@novalux.it](mailto:info@novalux.it) · VAT number 00536541204 · [novalux.com](http://novalux.com)  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.  
Last update: 4/7/2025, 16:39:20



# P-30 PCB

105897.20

## SCREENS

|                                                                                  |                            |           |
|----------------------------------------------------------------------------------|----------------------------|-----------|
|  | P-30: DIFF. OPALE L=6500   | 103315.99 |
|  | P-30: DIFF. OPALE PER L800 | 103360.99 |

## COMPLETION ACCESSORIES

|                                                                                     |                                          |           |
|-------------------------------------------------------------------------------------|------------------------------------------|-----------|
|    | P-30: ANGOLO L PLAFONE-SOSP-PARETE CAFFE | 103327.20 |
|    | P-30: COVER ANGOLO L CAFFE               | 103329.20 |
|  | P-30: TESTATE PLAF/SOSP/PAR/SPOT CAFFE   | 103361.20 |
|   | P-30: SNODO 3P PER PCB/STRIP CAFFE       | 105853.20 |
|   | P-30: SNODO NO CAVI CAFFE                | 105854.20 |

