


P-30 PCB

1058A1.21







Features

Use: Indoor
Type of installation: SUSPENDED, CEILING MOUNTED
Emission: ADJUSTABLE
Optics: SPOT
Beam: 34°
Colour: CAPPUCCINO
Dimming: NO
Emergency: NO
L: 800mm
A: 31mm
H: 31mm
Made in: ITALY
Warranty: 5 years

Tech data

Luminaire input power: 14.9W
Luminaire luminouse flux: 864lm
IP: 20
Insulation class: I
No. of driver per product: 1
Supply voltage: 220-240V 50/60Hz
SELV: Sì

Source

Light source: LED
Source power: 9W
Source luminous flux: 974lm
Colour temperature: 2700K
CRI: >90
Colour tolerance: 2 Step MacAdam
LED lifespan: 50000h L90 B10

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 1Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: CAM edilizia - Conforme al Decreto Ministeriale 23 giugno 2022 n.256 e 24 novembre 2025 n.256.

P-30 PCB: View more product info

Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV Gmbh

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 9/6/2026, 16:27:47

P-30 PCB




1058A1.21

novalux
ITALIAN LIGHTING DESIGN SINCE 1948


SCREENS

	P-30: DIFF. OPALE L=6500	**103315.99**

COMPLETION ACCESSORIES

	P-30: TESTATA PER INSTALL.VERT. CAP	**1058D8.21**
	P-30: COVER ANGOLO T CAPP	**103333.21**
	P-30: SNODO NO CAVI CAPP	**105854.21**
	P-30: ANGOLO T PLAFONE-SOSP CAPP	**103331.21**
	P-30: ANGOLO L PLAFONE-SOSP-PARETE CAPP	**103327.21**
	P-30: TESTATE PLAF/SOSP/PAR/SPOT CAPP	**103361.21**
	P-30: COVER ANGOLO L CAPP	**103329.21**
	P-30: SNODO 3P PER PCB/STRIP CAPP	**105853.21**

MOUNTING ACCESSORIES




	P-30: ROSONE LATER. ALIM L=1200 3P BIA	**103320.01**

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 9/6/2026, 16:27:47

P-30 PCB

1058A1.21

novalux
ITALIAN LIGHTING DESIGN SINCE 1948

	P-30: CAVO DI SOSPENSIONE	**103318.99**
	P-30: ROSONE LATER. ALIM L1200 3P CAPP	**103320.21**
	P-30: ROSONE QDR CARTON. L1200 3P CAPP	**103319.21**
	P-30: ROSONE QDR CARTON. L=1200 3P BIA	**103319.01**

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.

Last update: 9/6/2026, 16:27:47