




## Features

Use: Indoor  
Type of installation: TRACK  
Emission: ADJUSTABLE  
Optics: SPOT  
Beam: 38°  
Colour: WHITE  
Dimming: ON/OFF  
Emergency: NO  
L: 110mm  
A: Ø55mm  
H: 150mm  
Warranty: 5 years  
Weight: 0.444kg




## Tech data

Luminaire input power: 10W  
Luminaire luminous flux: 1189lm  
IP: 20  
Insulation class: II  
No. of driver per product: 1  
Supply voltage: 220-240V 50/60Hz  
SELV: Si

## Source

Light source: LED  
Source power: 10W  
Source luminous flux: 1426lm  
Colour temperature: 4000K  
CRI: >90  
LED lifespan: 50000h L80 B10



## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

## Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[DALi: View more product info](#)



**SCREENS**

---



DALI: LENTE F55 PER 10W

**106126.00**

---



DALI: LENTE F15 PER 10W

**106136.00**

**COMPLETION ACCESSORIES**

---



DALI: INSERTO ORO OPACO PER 10W

**106128.15**

---



DALI: HONEYCOMB PER 10W

**106127.02**