



Features

Use: Indoor
Type of installation: SUSPENDED, CEILING MOUNTED
Emission: DIRECT
Optics: BATWING
Colour: WHITE
Dimming: DALI
Emergency: NO
L: 1500mm
A: 70mm
H: 40mm
Warranty: 5 years
Weight: 2.35kg

Tech data

Luminaire input power: 53W
Luminaire luminous flux: 8086lm
IP: 40
Insulation class: I
No. of driver per product: 1
Supply voltage: 220-240V 50/60Hz

Source

Light source: LED
Source power: 46W
Source luminous flux: 8480lm
Colour temperature: 4000K
CRI: >80
LED lifespan: 50000h L70 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)

COMPLETION ACCESSORIES

| | | |
|---|---|------------------|
|  | LI-NEAR: MOD.TERMINALE L=210MM+TEST+SC | 107204.01 |
|  | LI-NEAR: TESTATE INIZIO-LINEA (COPPIA) | 107205.01 |
|  | LI-NEAR: MODULO CIECO 1,50M BIA+2 SCUR | 107206.01 |
|  | LI-NEAR: CONNETTORE 8 POLI CON MORSETTI | 107226.99 |
|  | LI-NEAR: GIUNTO A "L" 8 POLI | 107224.01 |
|  | LI-NEAR: GIUNTO A "T" 8 POLI | 107225.01 |
| MOUNTING ACCESSORIES | | |
|  | LI-NEAR: KIT SOSPENSIONE 3M 1 PZ. | 107207.99 |
|  | LI-NEAR: KIT FISSAGGIO PLAFONE (COPPIA) | 107209.99 |