



## Features

Use: Indoor  
Type of installation: SUSPENDED, CEILING MOUNTED  
Emission: DIRECT  
Optics: LINEAR LENS  
Beam: 90°  
Colour: WHITE  
Dimming: ON/OFF  
Emergency: Autonomy 1h/Recharge time 12h  
L: 1500mm  
A: 70mm  
H: 40mm  
Warranty: 5 years except battery  
Weight: 3.5kg

## Tech data

Luminaire input power: 53W  
Luminaire luminous flux: 8252lm  
Luminous flux in emergency: 11%  
IP: 40  
Insulation class: I  
No. of driver per product: 1  
Supply voltage: 220-240V 50/60Hz

## Source

Light source: LED  
Source power: 46W  
Source luminous flux: 8480lm  
Colour temperature: 4000K  
CRI: >80  
LED lifespan: 50000h L70 B20

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-22:2023

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)



## COMPLETION ACCESSORIES

	LI-NEAR: MOD.TERMINALE L=210MM+TEST+SC	<b>107204.01</b>
	LI-NEAR: TESTATE INIZIO-LINEA (COPPIA)	<b>107205.01</b>
	LI-NEAR: MODULO CIECO 1,50M BIA+2 SCUR	<b>107206.01</b>
	LI-NEAR: CONNETTORE 8 POLI CON MORSETTI	<b>107226.99</b>
	LI-NEAR: GIUNTO A "L" 8 POLI	<b>107224.01</b>
	LI-NEAR: GIUNTO A "T" 8 POLI	<b>107225.01</b>
<b>MOUNTING ACCESSORIES</b>		
	LI-NEAR: KIT SOSPENSIONE 3M 1 PZ.	<b>107207.99</b>
	LI-NEAR: KIT FISSAGGIO PLAFONE (COPPIA)	<b>107209.99</b>