

HALOS MINI

107348.02

novalux
ITALIAN LIGHTING DESIGN SINCE 1948



Features

Use: Indoor
Type of installation: WALL
Emission: INTERNAL
Optics: OPAL
Colour: BLACK
Dimming: WITH ACCESSORY
Emergency: NO
L: Ø 482mm
A: 20mm
H: 30mm
Made in: ITALY
Warranty: 5 years
Weight: 3kg

Tech data

Luminaire input power: 25.5W
Luminaire luminous flux: 1131lm
IP: 40
Insulation class: III
Supply voltage: MAX 1.4A
IK: 03
SELV: Si

Source

Light source: LED
Source power: 24W
Source luminous flux: 3388lm
Colour temperature: 2700K
CRI: >90
LED lifespan: 50000h L90 B10

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[HALOS MINI: View more product info](#)



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 6/8/2025, 12:51:17

HALOS MINI

107348.02

novalux
ITALIAN LIGHTING DESIGN SINCE 1948

ELECTRICAL ACCESSORIES



HALOS MINI VERTICALE: ALIM. ON/OFF 482

107324.99

DIMMABLE ACCESSORIES



HALOS MINI VERTICALE: ALIM. DA/PU 482

107325.99



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 6/8/2025, 12:51:17