



## Features

Use: Indoor  
 Type of installation: RECESSED INTO PLASTERBOARD, CEILING MOUNTED  
 Emission: DIRECT  
 Optics: OPAL  
 Colour: WHITE  
 Dimming: ON/OFF  
 Emergency: NO  
 H: 16mm  
 ø: Ø235  
 D: 65-205mm  
 Warranty: 5 years  
 Weight: 0.6kg

## Tech data

Luminaire input power: 14/17/20W  
 Luminaire luminous flux: 10W 1094/1173/1134  
 13W 1387/1516/1447  
 16W 1642/1826/1696lm  
 IP: 20  
 Insulation class: II  
 Supply voltage: 220-240V 50/60Hz  
 SELV: No

## Source

Light source: LED  
 Source power: 10W/13W/16W  
 Colour temperature: 3000K/4000K/5400K  
 CRI: >80  
 LED lifespan: 30000h L70 B20

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

[View more product info](#)

