



## Features

Use: Indoor  
 Type of installation: RECESSED INTO PLASTERBOARD, CEILING MOUNTED  
 Emission: DIRECT  
 Optics: OPAL  
 Colour: WHITE  
 Dimming: ON/OFF  
 Emergency: NO  
 L: 300mm  
 A: 300mm  
 H: 20mm  
 D: 65-254mm  
 Warranty: 5 years

## Tech data

Luminaire input power: 20/24/26W  
 Luminaire luminous flux: 16W 1682/1896/1749  
 20W 2015/2252/2093  
 22W 2191/2483/2280lm  
 IP: 20  
 Insulation class: II  
 Supply voltage: 220-240V 50/60Hz  
 SELV: No

## Source

Light source: LED  
 Source power: 16W/20W/22W  
 Colour temperature: 3000K/4000K/5400K  
 CRI: >80  
 LED lifespan: 30000h L70 B20

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

[View more product info](#)