

## Features

Use: Indoor  
 Type of installation: RECESSED INTO PLASTERBOARD  
 Emission: DIRECT  
 Optics: SPOT  
 Beam: 60°  
 Colour: SHINY CHROME  
 Dimming: PUSH, DALI  
 Emergency: WITH ACCESSORY  
 H: 99mm  
 ø: 228mm  
 Warranty: 5 years  
 Weight: 1.7kg

## Tech data

Luminaire input power: 34W  
 Luminaire luminous flux: 3043lm  
 Luminous flux in emergency: 1h: 13% / 3h: 5  
 IP: 40  
 Insulation class: II  
 Supply voltage: 220-240V 50/60Hz  
 UGR: <19  
 SELV: Si

## Source

Light source: LED  
 Source power: 32W  
 Colour temperature: 3000K  
 CRI: >90  
 LED lifespan: 50000h L90 B10

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

## Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: CAM edilizia - Conforme al Decreto Ministeriale 23 giugno 2022 n.256 e 24 novembre 2025 n.256.

## Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2012).

**COMPLETION ACCESSORIES**



---




SLIM: ADATT.PER FORO 240MM / 250MM

**11814.01**
**EMERGENCY ACCESSORIES**


---



THE PANEL 2: EMER.INC.1H 10/54VDC

**1020A4.99**

THE PANEL 2: EMER.INC.3H 10/54VDC

**1020A5.99**