



Features

Use: Indoor
 Type of installation: RECESSED INTO PLASTERBOARD
 Emission: DIRECT
 Optics: SPOT
 Beam: 24°
 Colour: GREY
 Dimming: PUSH, DALI
 Emergency: WITH ACCESSORY
 H: 99mm
 ø: 228mm
 Warranty: 5 years
 Weight: 1.7kg

Tech data

Luminaire input power: 34W
 Luminaire luminous flux: 3154lm
 Luminous flux in emergency: 1h: 13% / 3h: 5
 IP: 40
 Insulation class: II
 Supply voltage: 220-240V 50/60Hz
 UGR: <19
 SELV: Si

Source

Light source: LED
 Source power: 32W
 Colour temperature: 4000K
 CRI: >90
 LED lifespan: 50000h L90 B10

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: CAM edilizia - Conforme al Decreto Ministeriale 23 giugno 2022 n.256 e 24 novembre 2025 n.256.

Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2012).

COMPLETION ACCESSORIES



SLIM: ADATT.PER FORO 240MM / 250MM

11814.01**EMERGENCY ACCESSORIES**



THE PANEL 2: EMER.INC.1H 10/54VDC

1020A4.99

THE PANEL 2: EMER.INC.3H 10/54VDC

1020A5.99