



## Features

Use: Indoor  
Type of installation: RECESSED INTO PLASTERBOARD  
Emission: DIRECT  
Optics: SPOT  
Beam: 36°  
Colour: WHITE  
Dimming: ON/OFF  
Emergency: WITH ACCESSORY  
H: 78mm  
ø: 145mm  
D: 125-135mm  
Warranty: 5 years  
Weight: 0.7kg

## Tech data

Luminaire input power: 18.5W  
Luminaire luminous flux: (3K) 1547lm / (4K) 1577lm  
Luminous flux in emergency: 1h: 26% / 3h: 10%  
IP: 40  
Insulation class: II  
No. of driver per product: 1  
Supply voltage: 220-240V 50/60Hz  
UGR: <19  
IK: 8  
SELV: Si

## Source

Light source: LED  
Source power: 16W  
Colour temperature: 3000K/4000K  
CRI: >90  
LED lifespan: 50000h L90 B10

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

## Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.  
CAM edilizia: CAM edilizia - Conforme al Decreto Ministeriale 23 giugno 2022 n.256 e 24 novembre 2025 n.256.

[NIK: View more product info](#)

**EMERGENCY ACCESSORIES**

---



THE PANEL 2: EMER.INC.1H 10/54VDC

**1020A4.99**

---



THE PANEL 2: EMER.INC.3H 10/54VDC

**1020A5.99**