



Features

Use: Indoor
Type of installation: RECESSED INTO PLASTERBOARD
Emission: DIRECT
Optics: SPOT
Beam: 36°
Colour: GREY
Dimming: DALI2, PUSH
Emergency: WITH ACCESSORY
H: 78mm
ø: 145mm
D: 125-135mm
Warranty: 5 years
Weight: 0.8kg

Tech data

Luminaire input power: 18.5W
Luminaire luminous flux: (3K) 1521lm / (4K) 1550lm
Luminous flux in emergency: 1h: 26% / 3h: 10%
IP: 40
Insulation class: II
No. of driver per product: 1
Supply voltage: 220-240V 50/60Hz
UGR: <19
IK: 8
SELV: Si

Source

Light source: LED
Source power: 16W
Colour temperature: 3000K/4000K
CRI: >90
LED lifespan: 50000h L90 B10

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: CAM edilizia - Conforme al Decreto Ministeriale 23 giugno 2022 n.256 e 24 novembre 2025 n.256.

[NIK: View more product info](#)

EMERGENCY ACCESSORIES



THE PANEL 2: EMER.INC.1H 10/54VDC

1020A4.99



THE PANEL 2: EMER.INC.3H 10/54VDC

1020A5.99