



Features

Use: Indoor
Type of installation: CEILING MOUNTED
Emission: DIRECT
Optics: SPOT
Beam: 36°
Colour: WHITE
Dimming: ON/OFF
Emergency: NO
H: 157mm
ø: Ø170
Warranty: 5 years
Weight: 1.5kg

Tech data

Luminaire input power: 37W
Luminaire luminous flux: 3296lm
IP: 40
Insulation class: I
No. of driver per product: 1
Supply voltage: 220-240V 50/60Hz
SELV: Si

Source

Light source: LED
Source power: 32W
Colour temperature: 4000K
CRI: >90
LED lifespan: 50000h L80 B10

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2011).

[TIN: View more product info](#)