



Features

Use: Indoor
Type of installation: CEILING MOUNTED
Emission: DIRECT
Optics: SPOT
Beam: 36°
Colour: WHITE
Dimming: DALI2, PUSH
Emergency: NO
H: 143mm
ø: 120mm
Warranty: 5 years
Weight: 0.9kg

Tech data

Luminaire input power: 27W
Luminaire luminous flux: (3K) 1946lm / (4K) 2034lm
IP: 40
Insulation class: I
No. of driver per product: 1
Supply voltage: 220-240V 50/60Hz
UGR: <19
SELV: Si

Source

Light source: LED
Source power: 23W
Colour temperature: 3000K/4000K
CRI: >90
LED lifespan: 50000h L90 B10

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: CAM edilizia - Conforme al Decreto Ministeriale 23 giugno 2022 n.256 e 24 novembre 2025 n.256.

Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2011).

[TIN: View more product info](#)

