


FORTY8 TRACK

108585.02 + 108589.02

MICRO MOD. F8: 25W 2.7K 724 DALI C90 NE + RIFLETTORE M/O F8: NERO OPACO L=724



novalux
ITALIAN LIGHTING DESIGN SINCE 1948



Features

Use: Indoor
Type of installation: TRACK
Emission: DIRECT
Optics: MICRO OPTICS
Beam: 50°
Colour: BLACK
Dimming: DALI
Emergency: NO
L: 724mm
Warranty: 5 years
Weight: 0.47kg

Tech data

Luminaire input power: 30W
Luminaire luminous flux: 1860lm
IP: 20
Insulation class: III
No. of driver per product: 1
Supply voltage: 48 Vdc
UGR: <19
SELV: Sì

Source

Light source: LED
Source power: 25W
Colour temperature: 2700K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[FORTY8 TRACK: View more product info](#)



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 6/8/2025, 13:07:04

108585.02 + 108589.02

MICRO MOD. F8: 25W 2.7K 724 DALI C90 NE + RIFLETTORE M/O F8: NERO OPACO L=724



Features

Use: Indoor
Optics: MICRO OPTICS
Colour: BLACK
L: 724mm
Weight: 0.06kg

Tech data

UGR: <19

