



# T-48 MINI

108592.02

**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948



## Features

Use: Indoor  
Type of installation: TRACK  
Emission: DIRECT  
Optics: MICRO OPTICS  
Beam: 76°  
Colour: BLACK  
Dimming: DALI  
Emergency: NO  
L: 300mm  
A: 11mm  
H: 7mm  
Made in: ITALY  
Warranty: 5 years  
Weight: 0.025kg

## Tech data

Luminaire input power: 7W  
Luminaire luminous flux: 403lm  
IP: 20  
Insulation class: III  
Supply voltage: 48 Vdc  
UGR: <19  
SELV: Si

## Source

Light source: LED  
Source power: 5W  
Source luminous flux: 454lm  
Colour temperature: 4000K  
CRI: >90  
Colour tolerance: 3 Step MacAdam  
LED lifespan: 50000h L90 B20

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

## Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.  
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.  
Last update: 29/4/2024, 15:23:17