



Features

Use: Indoor
Type of installation: WALL, RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED, TRACK
Emission: DIRECT
Optics: OPAL FULL LIGHT
Colour: CAFFE
Dimming: ON/OFF
Emergency: NO
L: 2240mm
A: 53mm
H: 69mm
Made in: ITALY
Warranty: 5 years
Weight: 5.6kg

Tech data

Luminaire input power: 57.6W
Luminaire luminous flux: 4263lm
IP: 40
Insulation class: I
No. of driver per product: 2
Supply voltage: 220-240V 50/60Hz
SELV: Si

Source

Light source: LED
Source power: 48W
Colour temperature: 2700K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)

HERO

108605.20 + 108927.99

HERO: 48W 2.7K 2240 CAF + HERO: DIFF. OPALE TL PER 2240



novalux
ITALIAN LIGHTING DESIGN SINCE 1948



Features

Use: Indoor
Optics: OPAL FULL LIGHT
L: 2240mm
A: 52.5mm
H: 15mm
Made in: ITALY
Warranty: 5 years
Weight: 0.13kg

Tech data

IP: 40



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 8/4/2025, 12:17:08

COMPLETION ACCESSORIES

 Diagram showing a linear track lighting fixture with dimensions: H 135, L 250, W 33.	HERO: MOD.CIECO 250 CAF	108676.20
 Diagram showing a linear track lighting fixture with dimensions: H 135, L 1400, W 33.	HERO: MOD.CIECO 1400 CAF	108680.20
 Diagram showing an angled track lighting fixture with dimensions: H 135, L 150, W 33.	HERO: MOD.CIECO ANG.SX 150 CAF	108677.20
 Diagram showing a linear track lighting fixture with dimensions: H 135, L 1680, W 33.	HERO: MOD.CIECO 1680 CAF	108681.20
 Diagram showing two end caps for the track lighting fixture with dimensions: H 135, L 2, W 33.	HERO: COPPIA TESTATE CAF	108684.20
 Diagram showing an angled track lighting fixture with dimensions: H 135, L 150, W 33.	HERO: MOD.CIECO ANG.DX 150 CAF	108678.20
 Diagram showing a linear track lighting fixture with dimensions: H 135, L 1120, W 33.	HERO: MOD.CIECO 1120 CAF	108679.20

MOUNTING ACCESSORIES

 Diagram showing a suspension arm with dimensions: H 12, L 17.	HERO: SOSPL3000 1PZ. TESTA/CODA	108685.99
 Diagram showing two end caps for the track lighting fixture.	ALL-TRACK: COPPIA ADATT. 3P BIA	106722.01
 Diagram showing a power supply unit with dimensions: H 50, L 1200.	KIT ALIMENTAZIONE L1200 3P CAF	108919.20
 Diagram showing a power supply unit with dimensions: H 50, L 1200.	KIT ALIMENTAZIONE L1200 3P BIA	108919.01

HERO

108605.20 + 108927.99

HERO: 48W 2.7K 2240 CAF + HERO: DIFF. OPALE TL PER 2240

	ALL-TRACK: COPPIA ADATT. 3P NER	106722.02
	HERO: SPESS. CARTONG. 10MM 2PZ.	108689.99
	HERO: SOSPL3000 1PZ. UNIONE	108686.99
	HERO: STAFFA PARETE "L" CAF	108687.20
	HERO: SOSPL3000 1PZ TESTA W.G.ALTO	1086A1.99
	KIT ALIMENTAZIONE L3000 3P BIA	108920.01
	HERO: KIT INCASSO LED (1X)	108688.99
	HERO: SOSPL3000 1PZ UNIONE W.G.ALTO	1086A2.99
	KIT ALIMENTAZIONE L3000 3P CAF	108920.20