



Features

Use: Indoor
Type of installation: WALL, RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED, TRACK
Emission: DIRECT
Optics: MICRO OPTICS
Colour: WHITE
Dimming: ON/OFF
Emergency: NO
L: 1428mm
A: 53mm
H: 69mm
Made in: ITALY
Warranty: 5 years

Tech data

Luminaire input power: 40.5W
Luminaire luminous flux: 3638lm
IP: 40
Insulation class: I
No. of driver per product: 1
Supply voltage: 220-240V 50/60Hz
UGR: <19
SELV: Si

Source

Light source: LED
Source power: 36W
Colour temperature: 3000K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L90 B10

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2012).

[HERO: View more product info](#)



KIT ALIMENTAZIONE L1200 3P BIA 108919.01



HERO: SPESS. CARTONG. 10MM 2PZ. 108689.99



HERO: SOSPL3000 1PZ UNIONE W.G.BASSO 108686.99



HERO: SOSPL3000 1PZ TESTA W.G.ALTO 1086A1.99



KIT ALIMENTAZIONE L3000 3P BIA 108920.01



HERO: KIT INCASSO LED (1X) 108688.99



HERO: SOSPL3000 1PZ UNIONE W.G.ALTO 1086A2.99