

Features

Use: Indoor
Type of installation: WALL, RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED, TRACK
Emission: DIRECT
Optics: MICRO OPTICS
Colour: CAPPUCCINO
Dimming: ON/OFF
Emergency: NO
L: 1428mm
A: 53mm
H: 69mm
Made in: ITALY
Warranty: 5 years
Weight: 4.2kg

Tech data

Luminaire input power: 40.5W
Luminaire luminous flux: 4020lm
IP: 40
Insulation class: I
No. of driver per product: 1
Supply voltage: 220-240V 50/60Hz
UGR: <19
SELV: Sì

Source

Light source: LED
Source power: 36W
Colour temperature: 4000K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.


Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2012).

[View more product info](#)



COMPLETION ACCESSORIES



HERO: MOD.CIECO ANG.SX 150 CAP

108677.21



HERO: MOD.CIECO 1120 CAP

108679.21



HERO: MOD.CIECO 1680 CAP

108681.21



HERO: COPPIA TESTATE CAP

108684.21




HERO: MOD.CIECO 1400 CAP

108680.21



HERO: MOD.CIECO 250 CAP

108676.21



HERO: MOD.CIECO ANG.DX 150 CAP

108678.21

MOUNTING ACCESSORIES



HERO: SOSP.L3000 1PZ. TESTA/CODA

108685.99



ALL-TRACK: COPPIA ADATT. 3P BIA

106722.01



KIT ALIMENTAZIONE L1200 3P CAP

108919.21



KIT ALIMENTAZIONE L1200 3P BIA

108919.01

	ALL-TRACK: COPPIA ADATT. 3P NER	106722.02
	HERO: SPESS. CARTONG. 10MM 2PZ.	108689.99
	HERO: SOSPL3000 1PZ. UNIONE	108686.99
	KIT ALIMENTAZIONE L3000 3P CAP	108920.21
	HERO: SOSPL3000 1PZ TESTA W.G.ALTO	1086A1.99
	KIT ALIMENTAZIONE L3000 3P BIA	108920.01
	HERO: KIT INCASSO LED (1X)	108688.99
	HERO: SOSPL3000 1PZ UNIONE W.G.ALTO	1086A2.99
	HERO: STAFFA PARETE "L" CAP	108687.21