



## Features

Use: Indoor  
Type of installation: WALL, RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED, TRACK  
Emission: DIRECT  
Optics: OPAL  
Colour: CAFFE  
Dimming: PUSH, DALI  
Emergency: NO  
L: 2240mm  
A: 53mm  
H: 69mm  
Made in: ITALY  
Warranty: 5 years  
Weight: 5.6kg

## Tech data

Luminaire input power: 57.6W  
Luminaire luminous flux: 4294lm  
IP: 40  
Insulation class: I  
No. of driver per product: 2  
Supply voltage: 220-240V 50/60Hz  
SELV: Si

## Source

Light source: LED  
Source power: 48W  
Colour temperature: 4000K  
CRI: >90  
Colour tolerance: 3 Step MacAdam  
LED lifespan: 50000h L90 B10

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.  
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[HERO: View more product info](#)

# HERO

108658.20 + 108905.99

HERO: 48W 4K 2240 DALI CAF + HERO: DIFF. OPALE PER 2240



**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948



## Features

Use: Indoor  
Optics: OPAL  
L: 2240mm  
A: 48mm  
H: 6mm  
Made in: ITALY  
Warranty: 5 years  
Weight: 0.4kg

## Tech data

IP: 40



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: [info@novalux.it](mailto:info@novalux.it) · VAT number 00536541204 · [novalux.com](http://novalux.com)  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.  
Last update: 6/8/2025, 13:17:06

## COMPLETION ACCESSORIES

|                                                                                     |                                |           |
|-------------------------------------------------------------------------------------|--------------------------------|-----------|
|    | HERO: MOD.CIECO 250 CAF        | 108676.20 |
|    | HERO: MOD.CIECO 1400 CAF       | 108680.20 |
|    | HERO: MOD.CIECO ANG.SX 150 CAF | 108677.20 |
|    | HERO: MOD.CIECO 1680 CAF       | 108681.20 |
|    | HERO: COPPIA TESTATE CAF       | 108684.20 |
|  | HERO: MOD.CIECO ANG.DX 150 CAF | 108678.20 |
|  | HERO: MOD.CIECO 1120 CAF       | 108679.20 |

## MOUNTING ACCESSORIES

|                                                                                     |                                     |           |
|-------------------------------------------------------------------------------------|-------------------------------------|-----------|
|  | KIT ALIMENTAZIONE L1200 5P BIA      | 108921.01 |
|  | HERO: SOSPL3000 1PZ TESTA W.G.BASSO | 108685.99 |
|  | KIT ALIMENTAZIONE L3000 5P BIA      | 108922.01 |

|                                                                                                              |                                      |                  |
|--------------------------------------------------------------------------------------------------------------|--------------------------------------|------------------|
|                             | KIT ALIMENTAZIONE L3000 5P CAF       | <b>108922.20</b> |
|                             | HERO: SPESS. CARTONG. 10MM 2PZ.      | <b>108689.99</b> |
|                             | HERO: SOSPL3000 1PZ UNIONE W.G.BASSO | <b>108686.99</b> |
|                             | ALL-TRACK: COPPIA ADATT. 3P+DALI NER | <b>106723.02</b> |
|  | HERO: STAFFA PARETE "L" CAF          | <b>108687.20</b> |
|                            | ALL-TRACK: COPPIA ADATT. 3P+DALI BIA | <b>106723.01</b> |
|                           | HERO: SOSPL3000 1PZ TESTA W.G.ALTO   | <b>1086A1.99</b> |
|                           | KIT ALIMENTAZIONE L1200 5P CAF       | <b>108921.20</b> |
|                           | HERO: KIT INCASSO LED (1X)           | <b>108688.99</b> |
|                           | HERO: SOSPL3000 1PZ UNIONE W.G.ALTO  | <b>1086A2.99</b> |