


HERO

108690.20









Features

Use: Indoor
Type of installation: WALL, RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED, TRACK
Emission: DIRECT
Optics: SPOT
Beam: 34°
Colour: CAFFE
Dimming: NO
Emergency: NO
L: 1120mm
A: 53mm
H: 69mm
Made in: ITALY
Warranty: 5 years
Weight: 3.4kg

Tech data

Luminaire input power: 29W
Luminaire luminouse flux: 2144lm
IP: 40
Insulation class: I
No. of driver per product: 1
Supply voltage: 220-240V 50/60Hz
SELV: Sì

Source

Light source: LED
Source power: 2X13W
Source luminous flux: 2644lm
Colour temperature: 2700K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L90 B10

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards

Photobiological risk: RISK GROUP 1Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: CAM edilizia - Conforme al Decreto Ministeriale 23 giugno 2022 n.256 e 24 novembre 2025 n.256.

HERO: View more product info

Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV Gmbh



This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 9/6/2026, 16:35:20

HERO

108690.20

novalux
ITALIAN LIGHTING DESIGN SINCE 1948

COMPLETION ACCESSORIES

	HERO: MOD.CIECO 250 CAF	**108676.20**
	HERO: MOD.CIECO 1400 CAF	**108680.20**
	HERO: MOD.CIECO ANG.SX 150 CAF	**108677.20**
	HERO: MOD.CIECO 1680 CAF	**108681.20**
	HERO: COPPIA TESTATE CAF	**108684.20**
	HERO: MOD.CIECO ANG.DX 150 CAF	**108678.20**
	HERO: MOD.CIECO 1120 CAF	**108679.20**

MOUNTING ACCESSORIES

	HERO: SOSP.L3000 1PZ TESTA W.G.BASSO	**108685.99**
	ALL-TRACK: COPPIA ADATT. 3P BIA	**106722.01**
	KIT ALIMENTAZIONE L1200 3P CAF	**108919.20**

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 9/6/2026, 16:35:20

HERO

108690.20

	KIT ALIMENTAZIONE L1200 3P BIA	**108919.01**
	ALL-TRACK: COPPIA ADATT. 3P NER	**106722.02**
	HERO: SPESS. CARTONG. 10MM 2PZ.	**108689.99**
	HERO: SOSP.L3000 1PZ UNIONE W.G.BASSO	**108686.99**
	HERO: STAFFA PARETE "L" CAF	**108687.20**
	HERO: SOSP.L3000 1PZ TESTA W.G.ALTO	**1086A1.99**
	KIT ALIMENTAZIONE L3000 3P BIA	**108920.01**
	HERO: KIT INCASSO LED (1X)	**108688.99**
	HERO: SOSP.L3000 1PZ UNIONE W.G.ALTO	**1086A2.99**
	KIT ALIMENTAZIONE L3000 3P CAF	**108920.20**

Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV Gmbh

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 9/6/2026, 16:35:20