



Features

Use: Indoor
Type of installation: WALL, RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED
Emission: DIRECT
Optics: OPAL FULL LIGHT
Colour: CAFFE
Dimming: PUSH, DALI
Emergency: Autonomy 1h/Recharge time 12h
L: 1680mm
A: 53mm
H: 69mm
Made in: ITALY
Warranty: 5 years except battery

Tech data

Luminaire input power: 40.5W
Luminaire luminous flux: 3596lm
Luminous flux in emergency: 10%
IP: 40
Insulation class: I
No. of driver per product: 1
Supply voltage: 220-240V 50/60Hz
SELV: Si

Source

Light source: LED
Source power: 36W
Colour temperature: 4000K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L90 B10

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012, CEI EN 60598-2-22:2023

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[HERO: View more product info](#)

HERO

108698.20 + 108925.99

HERO: EM 36W 4K 1680 DALI CAF + HERO: DIFF. OPALE TL PER 1680



novalux
ITALIAN LIGHTING DESIGN SINCE 1948



Features

Use: Indoor
Optics: OPAL FULL LIGHT
L: 1680mm
A: 52.5mm
H: 15mm
Made in: ITALY
Warranty: 5 years
Weight: 0.13kg

Tech data

IP: 40



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 6/8/2025, 13:08:24

COMPLETION ACCESSORIES

 Diagram showing a linear light fixture with dimensions: H 135, L 250, W 33.	HERO: MOD.CIECO 250 CAF	108676.20
 Diagram showing a linear light fixture with dimensions: H 135, L 1400, W 33.	HERO: MOD.CIECO 1400 CAF	108680.20
 Diagram showing an angled light fixture with dimensions: H 135, L 150, W 33.	HERO: MOD.CIECO ANG.SX 150 CAF	108677.20
 Diagram showing a linear light fixture with dimensions: H 135, L 1680, W 33.	HERO: MOD.CIECO 1680 CAF	108681.20
 Diagram showing two end caps with dimensions: H 135, L 33, W 33.	HERO: COPPIA TESTATE CAF	108684.20
 Diagram showing an angled light fixture with dimensions: H 135, L 150, W 33.	HERO: MOD.CIECO ANG.DX 150 CAF	108678.20
 Diagram showing a linear light fixture with dimensions: H 135, L 1120, W 33.	HERO: MOD.CIECO 1120 CAF	108679.20

MOUNTING ACCESSORIES

 Diagram showing a mounting bracket with dimensions: H 12, L 17.	HERO: SOSPL3000 1PZ TESTA W.G.BASSO	108685.99
 Diagram showing a power supply unit with dimensions: H 50, L 50.	KIT ALIMENTAZIONE L3000 5P CAF	108922.20
 Diagram showing two pieces of cardboard with dimensions: H 10, L 100.	HERO: SPESS. CARTONG. 10MM 2PZ.	108689.99



HERO: SOSP.L3000 1PZ UNIONE W.G.BASSO

108686.99



HERO: STAFFA PARETE "L" CAF

108687.20



HERO: SOSP.L3000 1PZ TESTA W.G.ALTO

1086A1.99



KIT ALIMENTAZIONE L1200 5P CAF

108921.20



HERO: KIT INCASSO LED (1X)

108688.99



HERO: SOSP.L3000 1PZ UNIONE W.G.ALTO

1086A2.99